CLASSIC
WIRE & CABLE

Aluminum Building Wire

Aluminum building wire is widely used in conduit and cable tray installations for services, feeders, and branch circuits. CWC LowFriction® XHHW-2 and CWC LowFriction® THHN/THWN-2 support commercial, industrial, residential, and data center applications, delivering reliable power distribution and efficient installation performance.

CWC LowFriction®

Our Inventory

CWC LowFriction® XHHW-2 and CWC LowFriction® THHN/THWN-2 are stocked nationwide and available in red, blue, yellow, green, gray, purple, orange, brown, white, and black. Inventory is ready to ship quickly from our distribution centers across the country, with paralleling services available at each location to help simplify installation and improve jobsite efficiency.

WWW.CLASSICWIRE.COM

Count on Classic for CWC LowFriction®

CABLE CONSTRUCTION

XHHW-2

Aluminum Conductor
Annealed compact stranded AA-8000 series Aluminum Conductor Material (ACM).

Insulation
XHHW-2: Low coefficient of friction, abrasion, moisture, and heat resistant colored crosslinked polyethylene (XLPE).

THHN / THWN-2: Low coefficient of friction, abrasion, moisture, and heat resistant colored polyvinyl chloride (PVC).

Covering
Low coefficient of friction, abrasion, moisture, and heat resistant translucent Nylon polyamide.

THHN / THWN-2

WHY CLASSIC WIRE?

Engineered for Performance
Classic Wire's CWC LowFriction® XHHW-2 and CWC LowFriction® THHN/THWN-2 cable is manufactured and listed in accordance with UL standards and certifications.

Consistent Stock Availability
CWC LowFriction® XHHW-2 and CWC LowFriction® THHN/THWN-2 cable is stocked nationwide! We offer coast-to-coast delivery in 1-2 business days.

Trusted Across Markets
CWC LowFriction® XHHW-2 and CWC LowFriction® THHN/THWN-2 THHN/THWN-2 cable is trusted by customers across the industrial, data center, commercial, and renewable energy markets.

sales@classicwire.com

www.classicwire.com

800-298-3500